


INSTRUCTIONS

MOVEO TF-STRAP (Technical Fabric - Strap)

An auxiliary harness (15) is provided with the Moveo® brace neck brace made from high-tech fabric (TF-Strap) which allows the brace to be fastened to the user for both on-road (daily commutes or bicycle rides) and off-road use (motocross, mountain bike descents, etc.) without having to attach it to your clothing.

The TF-Straps (15) is attached to the neck brace by the fixation holes in the lower front of the brace (10) and another fixation hole in the central lower part at the back (10).



To ensure the harness is attached correctly, we recommend the following procedure:

- Before starting to connect it to the neck brace, widen the ring formed by the harness (15) to its maximum width. To do so, use the two adjustment buckles (16) on the TF-Strap (15), leaving the same length of strap on each side of the buckle (16).
- Next, open the Velcro® fastening system of the back strap (17), insert the strap through the fixation hole (10) at the bottom of the neck brace, and close the strap again, making sure the Velcro® is securely gripped.
- When the back strap (17) is attached, do the same with the two front straps (18), inserting them in the corresponding fixation holes (10) at the bottom of the front of the neck brace. Make sure the straps of the harness are not twisted.
- Open the front clip (19) of the TF-Strap and put on the neck brace as if you were putting on a rucksack, allowing the front clip (19) and adjustment buckles (16) of the TF-strap to fall over your chest underneath your arms.
- Once the brace is on, close the front clip (19) and adjust the length of the strap using the adjustment buckles (16) until you feel that it the harness is firmly secured to the body yet without exerting too much pressure.

